

# **EEAE**

#### DIE-CAST ALUMINUM LED EXIT SIGN

#### Illumination

- Ultra bright, energy efficient, long life Red or Green LED.
- New York City approved 8" EXIT letters.

**STANDARD** 











**OPTIONAL** 







### **Electrical**

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.


# **Mounting**


- Aluminum mounting canopy included for top or end mount.
- Universal K/O pattern on back plate for wall mount.

## Housing

- Premium-grade, aluminum housing (also available in black or white powder-coated finishes).
- Field selectable knockout chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.

### **Dimensions**





## **Options**

- **TP:** Tamper-proof hardware helps prevent unauthorized access to the unit.
- **SDT:** Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.
- **2C:** Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.

# Warranty / Listing



- Five year warranty on all electronics and housing.
  Battery pro rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations ( $0^{\circ}C 50^{\circ}C$ ).

#### **How To Order**

Sample Part Number: EEAE-1-R-B-A-EM

Model	N° Of Faces		Letter Color		Housing Color		Panel		Battery		Options	
EEAE	1	Single Face	R	Red	W	White	W	White	Blank	AC Only	SDT	Self-diagnostic <sup>1</sup>
	2	Double Face			В	Black	В	Black	Diam		2C	Dual Circuit <sup>2</sup>
		Double Fuel	G	Green	D Didok	Didok		Didok	EM	Battery Backup	TP	Tamper Proof
	3	Universal Single / Double Face			А	Aluminum	А	Aluminum			USA	Assembled in USA

Special voltage options available. Check with your Luxquild Lighting Representative.

<sup>&</sup>lt;sup>1</sup> Available only with EM units.

<sup>&</sup>lt;sup>2</sup> Available only with AC units.